

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208 Miami, Florida 33175-2474 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/pera/

# DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY AFFAIRS (PERA) BOARD AND CODE ADMINISTRATION DIVISION

# NOTICE OF ACCEPTANCE (NOA)

Marvin Windows and Doors Highway 11 West (P.O. Box 100) Warroad, MN 56763-0100

#### Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code. This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series "StormPlus IZ4 Clad Casemaster Picture" Aluminum Clad Wood Fixed Window - L.M.J.

**APPROVAL DOCUMENT:** Drawing No. 1536, titled "Clad Casemaster Picture StormPlus IZ4", sheets 1 through 10 of 10, dated 04/02/08, with revision A1 dated 10/17/11, prepared by W. W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren W. Schaefer, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section.

#### MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

**LABELING:** Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

**RENEWAL** of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

**TERMINATION** of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

**ADVERTISEMENT:** The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

**INSPECTION:** A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official. This NOA revises NOA # 08-0213.08 and consists of this page 1 and evidence pages E-1 and E-2, as well as approval document mentioned above.

The submitted documentation was reviewed by Manuel Perez, P.E.

MIAMI-DADE COUNTY
APPROVED

W

NOA No. 11-1021.10 Expiration Date: July 03, 2013 Approval Date: December 22, 2011 Page 1

# **Marvin Windows and Doors**

## NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

#### A. DRAWINGS

- 1. Manufacturer's die drawings and sections.
- Drawing No. 1536, titled "Clad Casemaster Picture StormPlus IZ4", sheets 1 through 10 of 10, dated 04/02/08, with revision A1 dated 10/17/11, prepared by W. W. Schaefer Engineering & Consulting, P.A, signed and sealed by Warren W. Schaefer, P.E.

#### B. TESTS

- 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
  - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
  - 3) Water Resistance Test, per FBC, TAS 202-94
  - 4) Large Missile Impact Test per FBC, TAS 201-94
  - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94

along with marked-up drawings and installation diagram of Storm Plus IZ4 Casemaster aluminum clad wood fixed window, Units 3, 8, 9, 11 & 12, prepared by Architectural Testing, Inc., ATI-77780.01-201-18, dated 01/28/08, signed and sealed by Joseph A. Reed, P.E.

(Submitted under NOA# 08-0213.08)

## C. CALCULATIONS

- Anchor verification calculations and structural analysis, complying with FBC-2007 and FBC-2010, prepared by prepared by W. W. Schaefer Engineering & Consulting, P.A., dated 02/14/08 and updated on10/17/11, signed and sealed by Warren W. Schaefer, P.E.
- 2. Glazing complies with ASTM E1300-04

## D. QUALITY ASSURANCE

1. Miami-Dade Department of Permitting, Environment, and Regulatory Affairs (PERA).

## E. MATERIAL CERTIFICATIONS

1. Notice of Acceptance No. 10-0413.04 issued to E.I. DuPont DeNemours & Co., Inc. for their "DuPont Sentry Glass® Interlayer" dated 05/26/10, expiring on 01/14/12.

Manuel Perez, P.B. Product Control Examiner NOA No. 11-1021.10

Expiration Date: July 03, 2013 Approval Date: December 22, 2011

## **Marvin Windows and Doors**

# NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

## F. STATEMENTS

- 1. Statement letter of conformance complying with the FBC-2007 and FBC-2010, dated October 17, 2011, signed and sealed by Warren W. Schaefer, P.E.
- 2. Statement letter of no financial interest, dated October 17, 2011, signed and sealed by Warren W. Schaefer, P.E.
- 3. Laboratory compliance letter for Test Report No. **ATI 77780.01-201-18** issued by Architectural Testing, Inc., dated 01/28/08, signed and sealed by Joseph A. Reed, P.E.
- 4. Test Proposal #07-3071 issued by BCCO dated 06/21/07, revised on 07/02/07, signed by Manuel Perez, P.E.

## G. OTHERS

1. Notice of Acceptance No. **08-0213.08**, issued to Marvin Windows and Doors for their Series "StormPlus IZ4 Casemaster" Aluminum Clad Wood Fixed Window – L.M.I., approved on 07/03/08 and expiring on 07/03/13.

Manuel Perez, R.F. Product Control Examiner NOA No. 11-1021.10

Expiration Date: July 03, 2013 Approval Date: December 22, 2011

# GENERAL NOTES:

1. THESE WINDOW SYSTEMS HAVE BEEN TESTED, ANALYZED & APPROVED FOR DESIGN PRESSURES NOT TO EXCEED THOSE SHOWN IN THE "ALLOWABLE DESIGN PRESSURE TABLE(S).

2. OPENINGS, BUCKING & BUCKING FASTENERS MUST BE PROPERLY DESIGNED & INSTALLED TO TRANSFER WIND LOADS TO THE STRUCTURE.

3. ALL HARDWARE & FASTENERS SHALL BE IN ACCORDANCE WITH THESE DRAWINGS & SHALL NOT VARY UNLESS SPECIFICALLY MENTIONED ON THE DRAWINGS. SPECIFIED ANCHOR EMBED TO BASE MATERIAL SHALL BE BEYOND WALL FINISH OR STUCCO.

4. THE DETAILS & SPECIFICATIONS SHOWN HEREIN REPRESENT THE PRODUCTS TESTED & PROPOSED FOR WATER, AIR, IMPACT, CYCLIC & UNIFORM STATIC AIR PRESSURE TESTING IN CONFORMANCE WITH THE FLORIDA BUILDING CODE PROTOCALS TAS-201, 202 & 203 FOR LARGE MISSILE IMPACT WINDOWS.

5. THESE WINDOW SYSTEMS HAVE BEEN DESIGNED IN ACCORDANCE WITH AND MEET THE REQUIREMENTS OF THE FLORIDA BUILDING CODE (FBC) INCLUDING HIGH VELOCITY HURRICANE ZONES (HVHZ).

6. IMPACT SHUTTERS ARE NOT REQUIRED WITH THESE WINDOWS.

7. ALL ANCHORS SECURING WINDOW FRAME TO PRESSURE TREATED BUCKS OR WOOD FRAMING SHALL BE CAPABLE OF RESISTING CORROSION CAUSED BY THE PRESSURE TREATING CHEMICALS IN THE WOOD.

8. DETERMINE THE POSITIVE & NEGATIVE DESIGN LOADS TO USE WHEN REFERENCING THESE DOCUMENTS IN ACCORDANCE WITH THE GOVERNING CODE AND GOVERNING WIND VELOCITY. FOR WIND LOAD CALCULATIONS IN ACCORDANCE WITH THE FLORIDA BUILDING CODE, A DIRECTIONALITY FACTOR OF KD = 0.85 MAY BE APPLIED PER THE ASCE-7 STANDARD.

9. NO INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE CERTIFICATION OF THIS PRODUCT.
WIND LOAD DURATION FACTOR CD = 1.6 WAS USED FOR WOOD SCREW ANALYSIS ONLY.

10. MATERIALS, INCLUDING BUT NOT LIMITED TO STEEL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF FLORIDA BUILDING CODE CHAPTER 20.

11. ALL WOOD MEMBERS OF WINDOWS THAT MAY POSSIBLY COME INTO CONTACT WITH MASONRY OR CONCRETE SUBSTRATES, ARE SUBJECT TO MOISTURE &/OR ARE SUBJECT TO THE OUTSIDE ENVIRONMENT SHALL BE OF AN APPROVED DURABLE SPECIES OR BE TREATED IN AN APPROVED METHOD WITH AN APPROVED PRESERVATIVE PER FBC SECTION 2326.

# CORNER CONSTRUCTION (STANDARD RECTANGULAR WINDOWS)

FRAME CORNERS: THE SIDE WOOD MEMBERS ARE BUTTED TO THE HEAD & SILL MEMBERS, SECURED WITH THREE(3) GS16 1/2 X 1 1/2" STAPLES THROUGH THE HEAD & SILL INTO THE JAMB & ONE(1) 14 GA. 1/2 X 2" STAPLE THROUGH THE JAMB INTO THE HEAD & SILL & SEALED WITH SEALANT.

FRAME CLADDING CORNERS: CLADDING IS MITERED TOGETHER & JOINED WITH A CORNER KEY PART NO. 37A.

SASH CORNERS: SASH MEMBERS ARE MORTISED & TENONED AND SECURED WITH ONE(1) GS16 X 1 1/8" STAPLE.

SASH CALADDING CORNERS: CLADDING IS MITERED TOGETHER & JOINED WITH A CORNER KEY PART NO. 37B.

# CORNER CONSTRUCTION (SHAPED WINDOWS)

FRAME CORNERS: THE SIDE WOOD MEMBERS ARE BUTTED TO THE HEAD & SILL MEMBERS & SECURED WITH

NO. 7 X 2" SCREWS (3 AT SQUARE CORNERS; 4 AT SHAPED CORNERS) AND SEALED WITH SEALANT.

FRAME CLADDING CORNERS: CLADDING IS MITERED TOGETHER & JOINED WITH A CORNER KEY PART NO. 37C WHICH IS

SCREWED CLAD TO KEY WITH 4 NO. 7 X 1/2" SCREWS (2 PER KEY LEG).

SASH CORNERS: SASH MEMBERS ARE BUTTED TOGETHER, JOINED WITH 2 NO. 7 X 2" TRIM HEAD SCREWS & SEALED WITH SEALANT.

SASH CALADDING CORNERS: MITER CUT, BUTTED TOGETHER AND SEALED WITH SEALANT

# CORNER CONSTRUCTION (WIDE SASH WINDOWS)


FRAME CORNERS: THE SIDE WOOD MEMBERS ARE BUTTED TO THE HEAD & SILL MEMBERS & SECURED WITH NO. 7 X 2" SCREWS (3 AT SQUARE CORNERS; 4 AT SHAPED CORNERS) AND SEALED WITH SEALANT.


FRAME CLADDING CORNERS: CLADDING IS MITERED TOGETHER & JOINED WITH A CORNER KEY PART NO. 37C WHICH IS SCREWED CLAD TO KEY WITH 4 NO. 7 X 1/2" SCREWS (2 PER KEY LEG).

SASH CORNERS: SASH MEMBERS ARE BUTTED TOGETHER, JOINED WITH ONE NO. 10 X 6" SCREW.

SASH CLADDING CORNERS: SQUARE CUT, BUTTED TOGETHER AND SEALED WITH SEALANT

FRAME ANCHOR REQUIREMENTS TABLE						
OPENING TYPE (SUBSTRATE)	FRAME/CLIP TO OPENING FASTENER TYPE	MINIMUM EMBED	MINIMUM EDGE DIST.			
FRAME SHEAR SCREWS						
MIN. 2X4 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 10 SMS OR WOOD SCREW	1 1/4"	3/4"			
MIN. 18 GA. 33 KSI METAL STUD	NO. 10 GR. 5 SELF TAP/DRILLING SCREW	FULL	1/2"			
MIN. 1/8" THK A36 STEEL	NO. 10 GR. 5 SELF TAP/DRILLING SCREW	FULL	1/2"			
MIN. 1/8" THK 6063-T5 ALUM.	NO. 10 GR. 5 SELF TAP/DRILLING SCREW	FULL	1/2"			
C-90 CMU/2500 PSI CONCRETE	(1) 1/4" CONCRETE SCREW	1 1/4"	2"			
INSTALLATION CLIP SCREWS						
MIN. 2X4 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 8 X 1 1/2" SMS	1 3/8"	1/2"			
MIN. 1/8" THK A36 STEEL	NO. 8 GR. 5 SELF TAP/DRILLING SCREW	FULL	1/2"			
MIN. 1/8" THK 6063-T5 ALUM.	NO. 8 GR. 5 SELF TAP/DRILLING SCREW	FULL	1/2"			
(1) CONCRETE SCREWS SHALL BE ELCO ULTRACONS, ELCO CRETE-FLEX, ITW RAMSET/RED HEAD TAPCONS, HILTI KWIK-CON II OR POWERS RAWL TAPPER (HARDENED STEEL OR S.S.).						





<u> </u>	ALLOWABLE WINDOW SIZE/PRESSURE TABLE (SINGLE STANDARD SASH WINDOW)										$\overline{\Box}$					
	(SINGLE STANDARD SASH WINDOW)															
MAX.	MAX.	ALI	_OWAB	LE PR	E PRESSURE (PSF)			MAX.	MAX.	ALLOWABLE PRESSURE (PSF)					F)	1
WINDOW FRAME	WINDOW FRAME		ASS		ASS	GL	ASS	WINDOW FRAME	WINDOW FRAME	GL	ASS	GL	ASS	T GL	ASS	1
LONG	SHORT	))	TION		IONS		IONS	LONG			OPTION OPTIONS		OPTIONS		-	
	DIMENSION		A"		B"		C"		DIMENSION		۹"		В"		C"	
(IN.)	(IN.)	POS.				POS.	NEG.	(IN.)	(IN.)				NEG.	_	NEG.	
	50	59.1	59.1		75.0	$\geq$	$\bowtie$		72	62.2	<del></del>	75.0	75.0	$\geq$	$\geq$	
	48	63.1	63.1	75.0	75.0	$\geq$	$\geq \leq$		66	66.8		75.0	75.0	$\geq <$	$\geq$	
144	42	75.0	75.0	75.0	75.0	$\geq$	$\geq$	90	60	72.1	72.1	75.0	<del></del>	$\geq$	$\geq$	
	36	75.0		75.0	80.0	$\geq$	$\geq \leq$		54	75.0	78.1	75.0	75.0	$\supset$	$\supset$	
	24	95.0		95.0	95.0	<u> </u>	85.0		52	75.0	80.0	75.0	80.0	$\times$	$\supset$	
	54	56.0	56.0	75.0	75.0	$\geq$	$\triangleright \triangleleft$		38	95.0	95.0	95.0	95.0	75.0	85.0	]
132	48	65.7	65.7	75.0	75.0	$\geq$	$\triangleright\!\!\!<$		72	67.5	67.5	75.0	75.0	X	$\times$	1
132	42	75.0	75.0	75.0	75.0	$\supset$	$\supset \subset$	İ	66	71.9	71.9	75.0	75.0	$\supset$		1
	39	75.0	80.0	75.0	80.0	$\supset$	$\supset \subset$	84	60	75.0	76.9	75.0	75.0	$\supset$	$\supset$	1
	26	95.0	95.0	95.0	95.0	75.0	85.0		56	75.0	80.0	75.0	80.0	$\supset$	$\triangleright$	1
	60	53.1	53.1	75.0	75.0	$\times$	$\supset \subset$		41	95.0	95.0	95.0	95.0	75.0	85.0	
	54	59.7	59.7	75.0	75.0				72	72.7	72.7	75.0	75.0	$\overline{}$	$\overline{}$	1
120	48	69.6	69.6	75.0	75.0			70	66	75.0	76.7	75.0		$\triangleright$	$\Longrightarrow$	1
	43	75.0	80.0	75.0	80.0	$\supset$		78	61	75.0	80.0	75.0	<del></del>	$\Longrightarrow$	$\Longrightarrow$	١
	28	95.0	95.0	95.0	95.0	75.0	85.0		44		95.0	95.0		75.0	85.0	
	66	55.2	55.2	73.6	73.6	$\supset$			72		78.2	75.0	75.0			
Ì	60	59.8	59.8	75.0	75.0	$\supset$		72	68	75.0		75.0	80.0	$\Longrightarrow$	$\langle \rangle$	
	54	66.4	66.4	75.0	75.0				48		95.0		95.0	75.0	85.0	
108	48	75.0	75.7	75.0	75.0	$\triangleright$			66	75.0		75.0				
	45	75.0	80.0	75.0	80.0	$\triangleright$		66	52		95.0			75.0	85.0	
Ì	36	95.0	95.0	95.0	95.0	75.0	85.0		60	75.0		75.0		75.0	30.0	
	72	58.6		75.0	75.0	$\overline{}$		60	57		95.0			75.0	85.0	
	66	62.5		75.0	75.0	$\Longrightarrow$	$\bowtie$	1 WINDOW						1	1 30.0	
	60	67.7	67.7	75.0	75.0	$\Longrightarrow$	$\bowtie$		SIZE DIMEN IALLER SIZE						) IAI I	
96	54	74.1	74.1	75.0	75.0	$\Longrightarrow$	$\bowtie$	TO THE NE	AREST LARC	SER SI	ZE SH	IOWN	IN TAF	BLE.	YUAL	
ŀ	49			75.0	80.0	$\Longrightarrow$	$\bowtie$		D OUT BOX							
	36	95.0		95.0	95.0	75.0	ACCEPTABLE FOR THE DECOFORING ADT									
<u> </u>				20.0	30.0	1	30,0	I					····		J	l

		BLE WIND SINGLE V						ABLE	
	MAX. WINDOW	MAX. WINDOW	т	.OWABI			<u> </u>	F)	-
	FRAME	FRAME	GL	ASS	GL	ASS	GL	ASS	1
	LONG	SHORT		ION	OPT	IONS	OPT	IONS	-
	DIMENSION		"/	4"	"ſ	3"	"(	l	
	(IN.)	(IN.)	POS.	NEG.	POS.	NEG.	POS.	NEG.	
	144	36	75.0	80.0	75.0	80.0	$\supset$	$\times$	1
	144	24	95.0	95.0	95.0	95.0	95.0	95.0	
	170	39	75.0	80.0	75.0	80.0	$\times$	$\times$	ĺ
	132	26	95.0	95.0	95.0	95.0	95.0	95.0	ı
	100	43	75.0	80.0	75.0	80.0	$\sim$	$\times$	
	120	28	95.0	95.0	95.0	95.0	95.0	95.0	
	108	48	75.0	80.0	75.0	80.0	$\sim$	$\sim$	ı
		32	95.0	95.0	95.0	95.0	95.0	95.0	
	96	54	75.0	80.0	75.0	80.0	$\times$	$\times$	
		36	95.0	95.0	95.0	95.0	95.0	95.0	
	90	58	75.0	80.0	75.0	80.0	> <	$\times$	
	90	38	95.0	95.0	95.0	95.0	95.0	95.0	
	84	62	75.0	80.0	75.0	80.0	$\times$	$\times$	
	04	41	95.0	95.0	95.0	95.0	95.0	95.0	
	79	67	75.0	80.0	75.0	80.0	> <	$\times$	
	78	44	95.0	95.0	95.0	95.0	95.0	95.0	
	72.625	72	75.0	80.0	75.0	80.0	> <	$\times$	ĺ
		48	95.0	95.0	95.0	95.0	95.0	95.0	
	66	66	75.0	80.0	75.0	80.0	> <	$\supset \subset$	
	00	52	95.0	95.0	95.0	95.0	95.0	95.0	
	60	60	75.0	80.0	75.0	80.0	> <	$\supset \subset$	
	00	57	95.0	95.0	95.0	95.0	95.0	95.0	

1. WINDOW SIZE DIMENSIONS SHOWN ARE MAXIMUM SIZES. SMALLER SIZES SHALL APPLY TO LOADS EQUAL TO THE NEAREST LARGER SIZE SHOWN IN TABLE.

2. CROSSED OUT BOXES DESIGNATE SIZES NOT ACCEPTABLE FOR THE RESPECTIVE OPTIONS.

SEE SHEET 8 FOR GLASS OPTIONS

SEE SHEET 8 FOR GLASS OPTIONS

STORMPLUS 124 PICTURE TITLE CASEMASTER <sup>0</sup> ¥ જ 2011

> DRAWING NO. 1536 SHEET NO.

3 of 10

CHECKED BY: W.W.S.

OATE: 04/02/08

LOT: 1=16

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No 11-1021.10
Expiration Date 1027 3, 2013

By Mauleb By Miami Dade Product Control


	MULLION A	LLOWABLE L	OAD TABLE	-			
MAXIMUM		ALLOWA	BLE PRES	SURE			
MULLION		(POS. & NEG. PSF)					
SPAN	WIDTH	NON-	D MULLION				
(IN.)	(IN.)	REINFORCED	4	6			
		MULLION	ANCHORS	ANCHORS			
<u> </u>	70		47.9				
il	72 66		49.8	57.2 59.4			
il	60		52.2	62.4			
	54			66.3			
96	48		55.5 59.9	71.5			
30	42		65.7	78.4			
i	36		73.7	88.0			
	30		85.1	95.0			
	24		95.0	95.0			
<u> </u>	72		53.2				
	66		55.0	63.6 65.7			
	60 54		57.5	68.6			
90	48		60.8 65.3	72.6			
90			71.4	78.0 85.3			
l	42 36						
		>	79.8	95.0			
	30		91.9	95.0			
·	24		95.0	95.0			
	72		59.9	71.5			
	66		61.5	73.4			
	60		63.9	76.3			
84	54		67.2	80.3			
	48		71.8	85.8			
	42		78.2	93.4			
	36		87.1	95.0			
	30		95.0	95.0			
1	72		68.4	81.7			
	66		69.7	83.2			
70	60		71.8	85.8			
78	54		75.1	89.7			
	48		79.8	95.0			
	42		86.4	95.0			
	36		95.0	95.0			
	72 OR MORE		79.8	95.0			
	66		80.4	95.0			
72	60		82.1	95.0			
	54		85.1	95.0			
	48		89.8	95.0			
	42	07.4	95.0	95.0			
	71 OR MORE	67.4	82.1	95.0			
	66	68.2	82.5	95.0			
	60	70.0	84.1	95.0			
71 1/8	54	72.5	87.1	95.0			
',	48	76.3	91.7	95.0			
	42	82.0	95.0	95.0			
	36	90.3	95.0	95.0			
	30	95.0	95.0	95.0			
	66 OR MORE	79.1	95.0	95.0			
i l			นรถ [	95.0			
	60	79.7	95.0				
66	60 54	81.8	95.0	95.0			
66	60 54 48	81.8 85.4	95.0 95.0	95.0 95.0			
66	60 54 48 42	81.8 85.4 91.1	95.0 95.0 95.0	95.0 95.0 95.0			
	60 54 48 42 36	81.8 85.4 91.1 95.0	95.0 95.0 95.0 95.0	95.0 95.0 95.0 95.0			
66 60 TABLE NO	60 54 48 42 36 60 OR MORE	81.8 85.4 91.1	95.0 95.0 95.0	95.0 95.0 95.0			

LESSER OF THE PRESSURE SHOWN IN THIS TABLE & THAT ALLOWED FOR THE INDIVIDUAL WINDOW SHALL CONTROL AS ALLOWABLE FOR THE OVERALL UNIT. 2. ADD 3/8" TO LOAD WIDTH VALUES IN THIS TABLE WHEN 3/8" ALUMINUM REINFORCEMENT PLATE IS USED.


3. CROSSED OUT BOXES DESIGNATE SIZES NOT ACCEPTABLE FOR THE RESPECTIVE OPTIONS.

FOR NON-REINFORCED MULLION CONDITIONS, SEE SECTIONS C1/7 & C3/7. FOR REINFORCED MULLION CONDITIONS, SEE SECTIONS C2/7 & C4/7.

# EXAMPLES OF SIDE-BY-SIDE SHAPED MULLED CONDITIONS



I. WINDOW SHAPES OTHER THAN THOSE SHOWN MAY APPLY PROVIDING THEY ARE APPLICABLE TO THOSE SHOWN ON SHEET 2. 2. SHAPED WINDOWS MAY ALSO BE MULLED TO RECTANGULAR WINDOWS AS TRANSOMS UNDER THE SAME RESTRICTIONS AS SIDE BY SIDE CONDITION SHOWN IN ELEVATION.



#### MULTIPLE UNIT NOTES:

1. FOR ALL DETAIL NOT SHOWN, SEE SINGLE WINDOW ELEVATIONS.

2. MULLION MAY BE HORIZONTAL OR VERTICAL PROVIDING WINDOW SIZES ARE RESTRICTED AS SHOWN IN THIS ELEVATION.


3. IF VERTICALLY STACKED, THE MANUFACTURER SHALL INSURE THAT THE DEAD LOAD WEIGHT OF THE

4. THERE IS NO LIMIT ON THE NUMBER OF WINDOWS THAT MAY BE COMBINED IN ONE DIRECTION INTO A VIDEN WINDOWS & THEIR MULLIONS.

5. INDIVIDUAL WINDOW SIZES SAME TO

5. INDIVIDUAL WINDOW SIZES SHALL BE AS SPECIFIED IN THE SINGLE WINDOW ELEVATION.

PRODUCT REVISED as complying with the Florida Acceptance No 11-1021.10 **Building Code** Expiration Date JULY 3, 2013



SHEET NO. **4** of

44135

ii: 1=16

**I**Z4


STORMPLUS


PICTURE


CASEMASTER


P.A. (CA 6809)

AIE: 04/02/08











OPTIONAL INSTALLATION CLIP DETAIL

(HEAD SECTION SHOWN, SILL & SIDES ARE INSTALLED THE SAME) (FOR DETAIL NOT SHOWN, SEE OTHER SECTIONS)




TYPICAL GLAZING DETAIL (RECTANGULAR WINDOW WITH STANDARD SASH)




OPTIONAL DIRECT MOUNT DETAIL TO SUBSTRATE WITH SPACER

(HEAD SECTION SHOWN, SILL & SIDES ARE INSTALLED THE SAME) (FOR DETAIL NOT SHOWN, SEE OTHER SECTIONS)



TYPICAL GLAZING DETAIL (SHAPED WINDOW WITH STANDARD SASH)



TYPICAL GLAZING DETAIL (RECTANGULAR OR SHAPED WINDOW WITH WIDE SASH)

# **GLASS OPTIONS**

GLASS OPTION A: 9/16" THICK LAMINATED GLASS (1/4" AN./0.09" DUPONT SG/1/4" AN.) GLASS OPTION B: 9/16" THICK LAMINATED GLASS (1/4" HT.ST./0.09" DUPONT SG/1/4" HT.ST.) GLASS OPTION C: 3/8" THICK LAMINATED GLASS (5/32" AN./0.090" DUPONT SG/5/32" AN.)


# **GLAZING OPTIONS**

GLAZING OPTION A: POLYOLEFIN FOAM WITH ACRYLIC ADHESIVE GLAZING TAPE AT EXTERIOR & INTERIOR WITH DOW 995 BACKFILL GLAZING OPTION B: GE RAPID STRENGTH EXTERIOR, INTERIOR & BACKFILL

PRODUCT REVISED as complying with the Florida **Building Code** Acceptance No 11

Miarii Dade Product Control

WILLER & Rail DOS TO TO THE STATE OF THE STAT



8 of 10

MARVIN WINDOWS
HIGHWAY 11; P.O.
WARROAD, MN

124

STORMPLUS


PICTURE

CASEMASTER

SLAD

CHECKED BY

OATE: 04/02/08



ITEM #	ITEM DESCRIPTION	MANUFACTURER/NOTES
	PARTS	,
1	JAMB (RECTANGULAR WINDOW HEAD & SILL)	* WOOD
2	JAMB (RECTANGULAR WINDOW SIDES)	* WOOD
3	JAMB (SHAPED WINDOW HEAD/SIDE)	LVL
4	JAMB (SHAPED WINDOW SIDES & SILL)	* WOOD
5	SASH (RECTANGULAR WINDOW)	* WOOD
6	SASH (SHAPED WINDOW)	* WOOD
7	FILLER BLOCK	* WOOD
. 8	SASH (WIDE SASH STILE & RAILS)	* WOOD
9	FILLER BLOCK	* WOOD
10	FILLER BLOCK	* WOOD
11	WINDOW STOP (RECTANGULAR WINDOW HEAD)	* WOOD
13	WINDOW STOP (SILL)	* WOOD
14	JAMB FILLER (SHAPED WINDOW HEAD)	LVL
19	WINDOW STOP (RECTANGULAR WINDOW SIDES)	WOOD
18	WINDOW STOP SKIN (SIDE JAMB)	WOOD VENEER
20	JAMB CLADDING (RECTANGULAR WINDOW)	6063-T5 ALUMINUM
21	JAMB CLADDING (SHAPED WINDOW)	6063-T5 ALUMINUM
22	STILE & RAIL CLADDING (RECTANGULAR WINDOW)	6063-T5 ALUMINUM
23	STILE & RAIL CLADDING (SHAPED WINDOW)	6063-T5 ALUMINUM
	NAIL FIN (RECTANGULAR HEAD)	6063-T5 ALUMINUM
	NAIL FIN	6063-T5 ALUMINUM
	NAIL FIN (SHAPED HEAD)	6063-T5 ALUMINUM
	WINDOW STOP (SHAPED WINDOW HEAD)	LVL
	GLASS STOP	* WOOD
	GLASS STOP	* WOOD
	MULLION CLIP	6063-T5 ALUMINUM
32	MULLION CLIP	6063-T5 ALUMINUM
33	MULLION REINFORCEMENT PLATE	6061-T6 ALUMINUM
	INSTALLATION C-CLIP	50 KSI GALV. STEEL
	FRAME CLAD CORNER KEY (RECTANGULAR WINDOWS)	
	SASH CLADDING CORNER KEY	5052 ALUMINUM
37C	FRAME CLAD CORNER KEY (SHAPED WINDOWS)	6063-T1 ALUMINUM


ITEM #	ITEM DESCRIPTION	MANUFACTURER/NOTES				
	PARTS					
	SEALS & SEALANTS					
51	SASH_WEATHERSTRIP	RIGID GLASS FILLED POLYPROPOLENE BY INTEK				
52	VINYL FRAME WEATHERSTRIP	BY AMSBURY				
53	THERMAL BREAK	BY AMSBURY				
54	CONNECTING BARB	PVC & GEON C70a0				
	MISC. FASTENERS					
58	F-18 x 1.125" BRAD NAIL	3" FROM CORNERS & MAX. 8" O.C.				
59	GSN 18 X 1/2" S.S. STAPLE	3" FROM CORNERS & MAX. 6" O.C.				
61	NO. 10-32 FH MACHINE SCREW	4 PER HINGE				
62	NO. 8 X 1" SMS	2 PER SNUBBER				
63	NO. 7 X 1/2" SMS	2 PER SNUBBER				
66	NO. 8 X 1" SMS	2" FROM ENDS & 5" TO 8" O.C.				
67	NO. 6 X 1" TRIM HEAD WOOD SCREW	2" FROM ENDS & 5" TO 8" O.C.				


<sup>\*</sup> ALL WOOD USED WITH TESTED UNITS IS MIN. GRADE 2 WESTERN PINE. ALTERNATE WOOD SPECIES TO PINE SHALL BE MIN. GRADE 2 WITH "E" = 1200000 PSI MIN. & "G" = 0.43 MIN

 ${\underline{\sf NOTE:}}$  ALL WOOD IS RECEIVED BY MARVIN WINDOWS & DOORS AS GRADE 2, BUT IS MACHINED BY MARVIN TO A SELECT GRADE USE.

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No 11-10 21-10
Expiration Date 1023,2013

By Molliel 1862 Miami/Dade Product Control





STORMPLUS 124

CHECKED BY: W.W.S.